

# **INTERRELATIONSHIP OF FAA-DOT-NASA PROGRAMS RELATING TO AIRCRAFT CABIN MATERIALS FIRE**

**C. SIMPSON**



**September 1973**

**STATUS REPORT**

Document is available to the public through the  
National Technical Information Service,  
Springfield, Virginia 22151

**DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION  
Systems Research & Development Service  
Washington D.C., 20590**

1. Report No. FAA-RD-73-146	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Interrelationship of FAA-DOT-NASA Programs Relating to Aircraft Cabin Materials Fire		5. Report Date September 1973	
		6. Performing Organization Code	
7. Author(s) Colin G. Simpson		8. Performing Organization Report No.	
9. Performing Organization Name and Address DEPARTMENT OF TRANSPORTATION Federal Aviation Administration Systems Research & Development Service Washington, D.C. 20590		10. Work Unit No.	
		11. Contract or Grant No.	
12. Sponsoring Agency Name and Address DEPARTMENT OF TRANSPORTATION Federal Aviation Administration Systems Research & Development Service Washington, D.C. 20590		13. Type of Report and Period Covered  Status Report	
		14. Sponsoring Agency Code ARD-520	
15. Supplementary Notes			
16. Abstract  Aircraft cabin materials fire hazards consisting of flammability, smoke emission, toxic gas emission and flash fire are discussed together with the work ongoing pertinent to these hazards by the FAA and other DOT Administrations and the NASA. The relationships among these efforts are considered together with funding estimates for FY 1974.			
17. Key Words Aircraft Materials      Toxicity Crash Fire Hazards Pyrolysis Smoke		18. Distribution Statement Document is available to the public through the National Technical Information Service, Springfield, Virginia 22151	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 20	22. Price

## TABLE OF CONTENTS

	Page
Introduction	1
Hazards of Cabin Fires	2
Materials Flammability	3
Burning Materials Smoke Emission	4
Burning Materials Toxic Gas Emission	5
Flash Fire	7
Cabin Fire Control and Extinguishment	8
Total Cabin Environment Protection	9
Funding Estimates	10
References and Bibliography	11

## INTRODUCTION

Post crash fires in transport aircraft are a major cause of fatalities in the air carrier segment of civil aviation. This report surveys the various hazards presented by such fires including the fire itself, smoke emission and toxic gas emission and their effect on cabin emergency evacuation.

The FAA and more recently the NASA both have E&D programs directed towards greater safety in the post crash fire environment. These efforts are presented to illuminate their complementary nature.

Future courses of action are outlined together with their probable impact on reducing cabin fire fatalities.

## HAZARDS OF CABIN FIRES

A recent survey of transport accidents over the 1952-1972 period shows that there were at least 182 accidents where post crash fire occurred.<sup>15</sup> In 60 of these, impact alone caused the 1953 fatalities. In the remaining 122, the 1015 fatalities are largely attributable to fire.

In a post crash situation the spilled fuel ignites with the flames entering the cabin by melting the aluminum skin, through breaks in the fuselage structure or through opened doors. These flames then ignite the cabin interior materials. The initial hazards are the fuel flames and the burning material flames. Mobile occupants will of course attempt to move away from these flames toward the exits.

Being fed by the external fuel fire, the burning cabin materials emit both smoke and toxic gases. The smoke presents two hazards; one, of reducing interior visibility making it difficult to see the exits and two, producing lachrymal effects and respiratory smoke poisoning.

Toxic gases are emitted in a wide variety including carbon monoxide, sulfur dioxide, hydrogen sulfide, hydrogen cyanide, hydrogen chloride, hydrogen fluoride and other hydrocarbons. These gases produce varied toxic effects with some causing incapacitation and death when inhaled in minute concentrations.

A later hazard that occurs sometimes is the phenomenon of flash fire. Although little explored to date, flash fires apparently occur when the mixture of gases and smoke filling the cabin are ignited and burn very rapidly throughout the cabin. Temperatures quickly reach over 1500°F which can be considered non-survivable. Flash fires have occurred in full scale fire tests and are suspected to have occurred in aircraft.

These hazards of material fire, smoke, toxic gases and flash fire vary in severity along the cabin length and vary in the time interval after crash at which they become incapacitating and then lethal. The fatalities they cause relate to how effectively the passengers and crew can exit the aircraft. In the recent Varig B-707 crash in Paris, these hazards occurred in flight with no exit possible. Fortunately this type of inflight fire is rare. That this particular B-707 was a cargo aircraft recently retrofitted with cabin seats and materials emphasized the urgency to upgrade the regulations covering cabin fires.

---

References in this report grouped under a combined Reference and Bibliography listing beginning on Page 11. Asterisks denote references in report.

## MATERIALS FLAMMABILITY

The initial approach to reducing the effects of cabin fire was to limit the flammability of cabin materials. Standards were established in 1947 limiting the horizontal burn rate of materials. Tests run at the National Aviation Facilities Experimental Center (NAFEC) in 1962 showed that many materials in use passed this standard but yet could cause fatal fires.<sup>1</sup> In 1967 these standards were made more stringent for some materials used in cabins and required these to be self extinguishing after the flame is removed. In 1972 these standards were applied to all cabin materials. These recent standards apply to newly certificated aircraft with the 1967 standards applying to older transports whenever they are refurbished by the airlines.

Further regulatory action planned by the Flight Standards Service, FAA, on cabin material flammability standards includes all older transports to meet these standards at some future date. The existing standards are considered adequate to control the rate at which cabin fires spread so that they can be extinguished by prompt action. Although self extinguishing in the small sample tests when the flame is removed, currently used materials can be burned when exposed to crash fuel fire or other fire sources.

The NASA has research underway for the development of more fire resistant cabin interior and cabin insulation materials.<sup>46</sup> In the past, such improved materials seldom met the airlines criteria of wear, maintenance, cost and weight to the extent that these materials would be adopted voluntarily by the manufacturers and the airlines. Such a state-of-the-art improvement would warrant consideration of increasingly stringent agency standards.

The National Highway Transportation Safety Administration has adopted vehicle cabin material flammability standards that are equivalent to the FAA's 1947 standards. These are felt to be adequate for ground vehicles.<sup>51</sup>

The United States Coast Guard has a modest annual program underway to specify non-flammable materials for floor coverings, etc., to prevent fire both from a personnel hazard standpoint and for protection of ship structural integrity.<sup>57</sup>

## BURNING MATERIALS TOXIC GAS EMISSION

The aviation community became more aware recently that toxic gas emissions from burning cabin interior materials constituted a hazard in transport crashes. Such awareness arose from the recent inclusion of tests for these toxic substances in autopsies of transport crash victims and their subsequent detection in significant quantities. This occurred during the accidents of Anchorage in 1970, New Haven in 1971 and Chicago O'Hare and Midway in 1972.

The first directed agency effort towards toxic gas analysis was the study by the National Bureau of Standards in 1968<sup>8</sup> in which both smoke and toxic gas emissions were measured for 141 samples of cabin materials. Massive industry full scale tests also were run in 1968<sup>53</sup> in which toxic gas concentrations were measured. A primary interest of these industry tests, however, was to evaluate both fire control and suppression techniques and smoke hoods, etc., for passenger protection. Little emphasis was placed on the reduction of toxic gas emissions by means of improved materials. The results of these agency and industry tests were insufficient to provide a basis for toxic gas regulatory standards.

A high priority project is in process at NAFEC to measure the toxic gas emissions from 60 currently used cabin materials. These data will enable issuance of a Notice of Proposed Rulemaking setting standards that eliminate the worst toxic gas producers. Full scale tests then will be conducted to measure toxic gas concentrations and distributions throughout the cabin and to relate these to the toxicological limits being developed by the Office of Aviation Medicine. These full scale tests then will be correlated to NBS Smoke Chamber gas emissions.

Recently both the NASA Johnson Space Center at Houston and Ames Research Center at Mountain View have been conducting material studies and full scale tests with the objective of developing improved cabin materials which possess flammability, smoke and toxic gas emission characteristics that should minimize the fire hazard potential in aircraft and spacecraft cabins. This work has been reasonably successful in terms of flammability but far from complete in terms of smoke, toxicity and practical use considerations. These new classes of polymers promise improvement, but much research remains to be done to bring them to the point of in-service use.

A new industry effort is underway by the Society of the Plastics Industry to study plastic material toxic gas emission. They are funding the National Bureau of Standards and the Southwest Research Institute to conduct tests which will be coordinated with the agency's work at NAFEC.



## FLASH FIRE

Not much is known yet about flash fires but they occur apparently when the combined mixture of smoke, gases and oxygen in the burning cabin environment reaches a temperature at which they ignite and burn throughout the entire cabin. Temperatures reach 1500° in less than a second and ignite the entire cabin. All the oxygen in the cabin is consumed. Survival in a flash fire is not considered possible.

Clearly, the flash fire phenomenon is related to material flammability and material smoke and gas emissions. The nature of this relationship is yet to be determined. The agency funded a laboratory study recently by the National Bureau of Standards to study flash fires specifically in relation to burning polyurethane foam cushions, a major smoke and gas emitter.<sup>16</sup> These tests indicated that smoke particles were essential to produce a flashover. Further work is planned at NBS on the physics of flash fires as part of a NAFEC project for FY 1973 and FY 1974 to investigate the relationship of flash fires to the flammability, smoke and toxic gas standards.

No NASA work is currently underway specifically related to aircraft flash fires.

## CABIN FIRE CONTROL AND EXTINGUISHMENT

The only new effort underway in this area is at NAFEC. The project on establishing the feasibility and effectiveness of an extinguishing agent distribution system throughout the cabin is scheduled for completion of testing against internal cabin fires by December 1974. Testing for effectivity against external fuel fires and preparation of a final report are due for completion by October 1975.

The project to examine the feasibility of cabin compartmentation as a means of isolating flash fires has been delayed by lack of funding and personnel until FY 1975. Completion of this work and provisions of data for rulemaking is scheduled for September 1975.

## TOTAL CABIN ENVIRONMENT PROTECTION

The existing agency standards on material flammability, the proposed standards on smoke emission and the future standards on toxic gas emission all are intended to contribute to a more survivable cabin environment that would permit safe egress. The agency proceeded to develop these standards in this order as a matter of relative priority and because funding did not permit simultaneous projects. A high priority effort has been assigned to NAFEC to develop a plan and carry-out full scale fire testing to determine which of these hazards is most critical to passenger safety and to determine the interaction among the hazards. This is a complex task because flame, smoke and toxic gases are unevenly distributed throughout the cabin, but ideally no one of them should be the dominant hazard.

When this information is known, the small scale NBS Chamber standards can be upgraded to match a full scale environment where all hazards are of equal but minimum severity. Cabin protection can then be increased to permit a longer egress period. This work will make an invaluable contribution to aviation safety.

The agency's effort described above is now being and will continue to be fully coordinated with the NASA efforts and industry efforts so that the respective goals of these groups can be met with maximum efficiency.

To summarize, the DOT goal and especially the FAA goal, is to perform E&D work on the various hazards associated with cabin fire to provide data that will support the issuance of airworthiness standards. Aircraft designed and constructed to these standards should provide a survivable environment during cabin fires. The NASA goal is to conduct basic research on improved cabin materials technology so that industry can develop and apply these materials to aircraft designs. Cooperation between the FAA and NASA personnel results in mutual use of all data generated to assist each agency to attain its goal.

FUNDING ESTIMATES

	<u>FY 1974</u> \$000
Department of Transportation	
Federal Aviation Administration	
Systems Research & Development Service	260
Office of Aviation Medicine	44
United States Coast Guard	30
National Aeronautics & Space Administration	250

## REFERENCES AND BIBLIOGRAPHY

### FEDERAL AVIATION ADMINISTRATION

#### REPORTS

- \* 1. Marcy, John F.; Nichols, E B; and DEMAREE, J. E.  
Flammability and Smoke Characteristics of Aircraft Interior Materials Technical Report ADS-3, January 1964
- \* 2. Marcy, John F. A Study of Air Transport Passenger Cabin Fires and Materials Technical Report ADS-44, December 1965
- 3. Gassman, Julius J. Characteristics of Fire in Large Cargo Aircraft Technical Report ADS-73, March 1966
- \* 4. Gross, D.; Loftus, J. J.; Lee, T. G.; and Gray V. E.  
Smoke and Gasses Produced by Burning Aircraft Interior Materials National Bureau of Standards Report NA-68-36, June 1968
- 5. Marcy, John F. and Johnson, Richard Flaming and Self Extinguishing Characteristics of Aircraft Cabin Interior Materials Report NA-68-30, July 1968
- 6. Gassman, Julius Characteristics of Fire in Large Cargo Aircraft (Phase II) Report FAA-RD-70-42, September 1970
- 7. Marcy, John F., Air Transport Cabin Mockup Fire Experiments Report FAA-RD-70-81, December 1970
- \* 8. Higgins, E. Arnold; Fiorica, Vincent; Thomas, A. A.; Davis, Harvey V. The Acute Toxicity of Brief Exposures to HF, HCl, NO<sub>2</sub> and HCN Singly and in Combination With CO Report FAA-AM-71-41, November 1971
- 9. Sarkos, Constantine P. Small Scale Fire Tests of High Temperature Cabin Pressure Sealant and Insulating Materials Report FAA-RD-71-67, November 1971

---

\* References in report

10. Darmer, Kenneth I. Short Term Animal Exposure to Carbon Monoxide and Hydrogen Cyanide Singly and in Combination Report FAA-AM-73-15, December 1972
11. Carbon Monoxide and Cyanide Hazards in Air Transport Accidents Accompanied by Fire  
Office of Aviation Medicine, January 29 1973
12. Jones, Jack and Sarkos, Constantine P. Design Calculations for a Halon 1301 Distribution Tube for an Aircraft Cabin Fire Extinguishing System  
Report FAA-RD-73-32, April 1973
13. Compartment Interior Materials Gas Emission  
Draft Advance Notice of Proposed Rulemaking  
14 CFR Part 25
14. Smoke Emission from Compartment Interior Materials In Transport Category Airplanes  
14 CFR Part 25, Docket No. 9611
- \* 15. Miller, J. Melvin Crash Fire-Fuel Survey Involving Turbine Powered Airplanes  
Report No. AFS-140-73-3, June 1973
- \* 16. Paabo, Maya; Comeford, J. J. A Study of the Decomposition Products of Polyurethane Foam Related to Aircraft Cabin Flash Fires  
Report No. RD-73-46, July 1973
17. Einhorn, I. N. Phisio-Chemical Study of Smoke Emission by Aircraft Interior Materials, Part I Physiological and Toxicological Aspects of Smoke During Fire Exposure University of Utah  
Report No. RD-73-50, 1, July 1973
18. Einhorn, I. N. Physio-Chemical Study of Smoke Emission by Aircraft Interior Materials, Part II Rigid and Flexible Urethane Foams University of Utah  
Report No. RD-73-50, 11, July 1973
- \* 19. Lopez, Edward L. Study of Smoke Emission from Burning Cabin Materials and the Effect on Visibility in Wide Body Jet Transports Lockheed Aircraft Corp.  
Draft Report No. RD-73-127

DATA REPORTS - NAFEC

20. No. 15 Flammability Characteristics of Boeing Aircraft Interior Materials - March 1966
21. No. 16 Flame Resistance of Airline Stewardess Uniform Clothing - March 1966
22. No. 39 Combustible Characteristics of Cabin Interior Materials - June 1967
23. No. 43 Flammability of Selected Interior Materials in FAA's Jet Star and Gulf Stream Airplanes - March 1968
24. No. 47 Supplementary Radiant Panel Test Data - January 1969
25. No. 51 Flash-Point and Thermal Degradation of Selected Interior Materials - January 1969
26. No. 69 Evaluation of Fluorel Coating for Aircraft Interior Materials - May 1970
27. No. 70 Evaluation of AVCO/NASA Rigid Foam as a Fire Barrier for Cabin Protection - April 1970
28. No. 71 Evaluation of Fluorel Coating for Aircraft Fire Barrier Application - April 1970
29. No. 76 Analysis of Industry Furnished Smoke Emission Data on New Cabin Interior Materials - October 1970  
Revised January 1971
30. No. 79 Summary of Class A Materials Fire Extinguishing Tests Using Liquid Nitrogen in a Closed, Non-Ventilated and Insulated Trailer - July 1970
31. No. 80 Some Effects from Cabin Pressure Sealants and Insulations on a Non-Melting Fuselage Environment During a Post-Crash Fire - January 1971
32. No. 81 Description of Special Laboratory Fire Test Equipment - February 1971

- 33. No. 82 Investigation of the Flammability Characteristics of Interior Materials from an FAA, DC3 Aircraft - February 1971
- 34. No. 83 Effects of the Insecticide Dichlorvos Spray on the Flammability of Aircraft Interior Materials - March 1971
- 35. No. 85 Flammability and Smoke Generation Studies of Air Force Litter Pads and Pillows - April 1971
- 36. No. 86 Flammability and Smoke Tests of FAA Aircraft Interior Materials - June 1971
- 37. No. 89 Flammability, Smoke, and Toxic Gas Test of AVCO Glass Reinforced Armor Panels - January 1972
- 38. No. 90 Flammability, Smoke, and Toxic Gas Tests of a Glass Fiber Carpet - February 1972
- 39. No. 91 Air Transport Cabin Mockup Smoke Studies - February 1972
- 40. No. 93 Evaluation of Fire Test Coating on Urethane Seat Foam in Aircraft - May 1972
- 41. No. 96 Flammability of Airline Stewardess Uniform Fabrics - August 1972
- 42. No. 97 Tables of Materials Tested at NAFEC for Use as Transport-Type Aircraft Interiors - July 1972
- 43. No. 98 Smoke Emission by Burning Aircraft Wiring - December 1972



NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

44. Non-metallic Material Design Guidelines and Test Data Handbook NASA-MSC-02681 May 29 1970
45. Einhorn, I. N.; Seader, J. D.; Muhlfeith, C. M.; Drake, W. O. Flammability and Toxicological Characteristics of Isocyanurate Foams, Intumescent Coatings and Fluorel University of Utah NASA NA52-6063, March 1971
- \* 46. Kourtides, D. A. and Parker, T. A. Chemical Research Projects Office: Functions, Accomplishments and Programs NASA TM X-62,186, September 1972
47. Kuvshinoff, Boris W.; McLeod, Stephen B.; Katz, Richard G. Directory of Workers in the Fire Field NACA CR-121149, February 1973
48. Heine, Donald A. and Brennaman, James J. The Cleveland Aircraft Fire Tests July 24 and 25, 1968
49. Pinkel, I. and Preston, G. M. Mechanism of Start and Development of Aircraft Crash Fires NASA Report 1133, 1954
50. Pacidrek, K. L.; Fratzer, R. H.; Kaufman, J. Fundamental Ignition Study for Material Fire Safety Improvement Dynamic Science Corp. NASA CR 114402, May 1972

NATIONAL HIGHWAY TRANSPORTATION SAFETY ADMINISTRATION

- \* 51. Flammability of Interior Materials in Passenger Cars,  
Multipurpose Passenger Vehicles, Trucks and Busses  
49 CFR 571, December 1970

AEROSPACE INDUSTRIES ASSOCIATION

- 52. Technical Summary - Crashworthiness Development Program  
Report AIA CDP-5
- \* 53. Fire Suppression and Smoke and Fume Protection -  
Crashworthiness Development Program  
Report AIA CDP-2, July 1965
- 54. Lighting and Exit Awareness - Crashworthiness  
Development Program  
Report AIA CDP-3, July 1968
- 55. Evacuation - Crashworthiness Development Program  
Report AIA CDP-4
- 56. Recommended Regulation Changes - Crashworthiness  
Development Program Report AIA CDP-RC, July 1968

UNITED STATES COAST GUARD

- \* 57. Materials - Deck Coverings for Merchant Vessels, Structural Insulations, Bulkhead Panels and Interior Finishes for Merchant Vessels  
46 CFR 164 Shipping
- 58. Report of Test on Comparative Non-combustibility Tests on Five Mineral Wool Insulation Materials for U.S. Coast Guard  
Report No. FR3843 National Bureau of Standards, Washington, D. C. May 1973
- 59. Report of Test on Reheating Test of Mineral Wool and Glass Fibre Insulation Materials for U.S. Coast Guard  
Report No. TG10210-2193: FR3730 National Bureau of Standards Washington, D. C. May 1970
- 60. Non-combustibility of Mineral Wool and Glass Fiber Insulation Materials  
Report No. 9988 National Bureau of Standards, Washington, D.C. February 1969
- 61. Report of the Ad-Hoc Working Group on Fire Test Procedures  
Inter-Governmental Maritime Consultative Organization  
December 1969